




# HASTINGS DATA LOGGERS

Australia's portable data logging specialists

## Fast response thermistor probe PB-4740


Issue 1 : 23rd September 2011 (E&OE)



### Sensor Specification

**Measuring Range** -40°C to +125°C (-40°F to +257°F)  
**Sensor Type** 10K NTC Thermistor

### Sensor Accuracy



### Physical Specification

**IP Rating** IP68 (waterproof)  
**Weight** 48g / 1.7oz

**Response time**  
**Water** 10 seconds (to 90% FSD)

**Probe**  
**Material** Stainless steel  
**Temperature rating** -40° to +125°C (-40°F to +257°F)

**Cable**  
**Material** Silicone rubber  
**Temperature rating** -60° to +200°C (-76° to +392°F)

**Connector**  
**Material** Nickel plated Brass/Zinc alloy  
**Temperature rating** -25° to +85°C (-13° to +185°F)

### Approvals

This probe is manufactured by Temperature Controls Sydney who operate a Quality Management system which conforms to ISO 9001.

### Related Products

This probe is suitable for use with the following products:

#### Tinytag Ultra 2 model numbers:

TGU-4020, TGU-4510

#### Tinytag Plus 2 model numbers:

TGP-4020, TGP-4510, TGP-4520

#### Tinytag View 2 model numbers:

TV-4020, TV-4510

data sheet