




# HASTINGS DATA LOGGERS

Australia's portable data logging specialists

## Standard PT1000 probe PB-5230


Issue 1 : 23rd September 2011 (E&OE)



### Sensor Specification

**Measuring Range** -200°C to +100°C (-328°F to +212°F)  
**Sensor Type** PT1000 (ClassA)

### Sensor Accuracy



### Physical Specification

**IP Rating** IP68 (waterproof)  
**Weight** 62g / 2.19oz

**Response time**  
**Water** 20 seconds (to 90% FSD)

**Probe**  
**Material** Stainless steel  
**Temperature rating** -200° to +100°C (-328°F to +212°F)

**Cable**  
**Material** PTFE (Teflon)  
**Temperature rating** -200° to +100°C (-328° to +212°F)  
 \*See Notes

**Connector**  
**Material** Nickel plated Brass/Zinc alloy  
**Temperature rating** -25° to +85°C (-13° to +185°F)

### Notes

\* Do not flex cable in temperatures below -100°C as it may become brittle.

### Related Products

This probe is suitable for use with the following products:

#### Tinytag Plus 2 model numbers:

TGP-4204

#### Tinytag View 2 model numbers:

TV-4204

### Approvals

This probe is manufactured by Temperature Controls Sydney who operate a Quality Management system which conforms to ISO 9001.

data sheet